

Package: RGenetics (via r-universe)

August 23, 2024

Title R packages for genetics research
Description R packages for genetics research
Version 0.1
Date 2013-11-06
Author Felix Yanhui Fan <nolanfyh@gmail.com>
Maintainer Felix Yanhui Fan <nolanfyh@gmail.com>
License GPL (>= 2)
NeedsCompilation no
Date/Publication 2013-11-06 18:10:48
Repository <https://felixfan.r-universe.dev>
RemoteUrl <https://github.com/cran/RGenetics>
RemoteRef HEAD
RemoteSha 4a8c638998efbb2dbecb1f28c234e9460af932fc

Contents

codonToAAone	2
codonToAAoneRNA	2
codonToAAthree	3
codonToAAthreeRNA	3
geneticCodeTable	4
Index	5

codonToAAone

Translating Codons to Amino Acids

Description

Translate a DNA 3-character codon to an amino acid (one character)

Usage

```
codonToAAone(codon)
```

Arguments

codon a DNA 3-character codon

See Also

[codonToAAthree](#)

Examples

```
codonToAAone('AAA')
```

codonToAAoneRNA

Translating Codons to Amino Acids

Description

Translate a RNA 3-character codon to an amino acid (one character)

Usage

```
codonToAAoneRNA(codon)
```

Arguments

codon a RNA 3-character codon

See Also

[codonToAAthreeRNA](#)

Examples

```
codonToAAoneRNA('AAA')
```

codonToAAthree	<i>Translating Codons to Amino Acids</i>
----------------	--

Description

Translate a DNA 3-character codon to an amino acid (three character)

Usage

```
codonToAAthree(codon)
```

Arguments

codon a DNA 3-character codon

See Also

[codonToAAone](#)

Examples

```
codonToAAthree('AAA')
```

codonToAAthreeRNA	<i>Translating Codons to Amino Acids</i>
-------------------	--

Description

Translate a RNA 3-character codon to an amino acid (three character)

Usage

```
codonToAAthreeRNA(codon)
```

Arguments

codon a RNA 3-character codon

See Also

[codonToAAoneRNA](#)

Examples

```
codonToAAthreeRNA('AAA')
```

<code>geneticCodeTable</code>	<i>Genetic Code Table</i>
-------------------------------	---------------------------

Description

DNA Genetic Code Table

Usage

```
geneticCodeTable(DNA = TRUE)
```

Arguments

DNA if 'TRUE', DNA code will be used, else, 'RNA' code will be used. Default is 'TRUE'

See Also

[codonToAAone](#)

[codonToAAthree](#)

[codonToAAoneRNA](#)

[codonToAAthreeRNA](#)

Examples

```
geneticCodeTable()  
geneticCodeTable(DNA=FALSE)
```

Index

`codonToAAone`, [2](#), [3](#), [4](#)
`codonToAAoneRNA`, [2](#), [3](#), [4](#)
`codonToAAthree`, [2](#), [3](#), [4](#)
`codonToAAthreeRNA`, [2](#), [3](#), [4](#)
`geneticCodeTable`, [4](#)